








# CROSS REFERENCE ACCESS DOOR

1

## ACCESS DOORS (GP, UAD, BASIC, AL, GP LV, GP VIS, RP)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p><b>WBCA GP 100 Series</b></p>	<p><b>WBCA's number 1 specified door!</b>  <b>General Purpose Premium</b>, 14 ga. door, fully concealed offset hinge up to and including 24x24. Laser cut. Cam latch opens with screwdriver.  <b>Meets all architectural specifications.</b></p>	UF-5000	B-NT	NA	DW 16 GA	DSC-214M	TM	L-MPG	UA	3202 (M)	NT
 <p><b>WBCA UAD 200 Series</b></p>	<p><b>Utility, Meets most architectural specifications.</b> 16 ga. steel. Trim 1-1/2" wide, Full length semi-concealed piano hinge. Laser cut. Cam latch opens with screwdriver.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA BASIC 300 Series</b></p>	<p><b>The Contractor's Door.</b>  <b>Our most Economical Door.</b> 18 ga. steel (up to &amp; including 16" x 16") and 16 ga. steel (18" x 18" - 24" x 24") Pin Lug hinge. Cam latch opens with screwdriver.</p>	NA	NA	AHD	NA	MC	NA	NA	NA	NA	NA
 <p><b>WBCA AL 1500 Aluminum Series</b></p>	<p><b>Lightweight, insulated.</b> Concealed continuous piano type hinge, insulated with 1" TUFF-R polyisocyanurate.  <b>All aluminum.</b></p>	LT 4000	NA	PAL	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA GP LV 100 Series</b></p>	<p><b>SPECIAL - with louvers.</b> 14 ga. Steel door. Trim is 1-1/2" wide, Fully-concealed hinge up to and including 24 x 24. Laser cut.  <b>Available in WBCA UAD.</b></p>	NA	NA	AHD LOUVER	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA GP VIS 100 Series</b></p>	<p><b>SPECIAL - Full glass</b> in 14 ga. door, Fully-concealed hinge up to and including 24 x 24. Laser cut</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA RP 110 Series</b></p>	<p><b>Removable Panel.</b> Same quality features as the WBCA Premium door. For use in confined areas. Door is 14 ga. steel. Trim 1-1/2" wide. Laser cut. Cam latches opens with screwdriver.</p>	PA-3000	NA	NA	NA	WSR SERIES	NA	NA	NA	NA	NA



### WILLIAMS BROTHERS CORPORATION OF AMERICA








Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502  
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: [www.wbdoors.com](http://www.wbdoors.com)

For country of manufacture of all Williams Brothers products please call us or visit our website at [www.wbdoors.com](http://www.wbdoors.com)

# CROSS REFERENCE ACCESS DOOR

2

## ACCESS DOORS (SMP, DW, RDW, PL, AP, AT, ATR)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <b>WBCA SMP 120 Series</b>	<b>Surface Mounted.</b> 14 ga. steel. Trim 1-1/2" wide. Full length piano hinge allows door to open to 180°	<b>SF-2000</b>	NA	<b>SFM</b>	<b>SF</b>	<b>DSC-214SM</b>	NA	NA	<b>MI-SF</b>	NA	NA
 <b>WBCA DW 400 Series</b>	<b>Drywall Bead.</b> 14 ga. Steel, Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes	<b>DW-5040</b>	<b>AHD GYP</b>	<b>B-NP</b>	<b>DWB</b>	<b>KDW</b>	<b>WB</b>	<b>L-DWB</b>	<b>MDW</b>	<b>3023 (DW)</b>	<b>NM</b>
 <b>WBCA RDW 410 Series</b>	<b>Recessed-Drywall Bead.</b> 14 ga. steel, 1" recessed depth accommodates drywall. Frame is 16 ga. Steel, 1" wide perforated flange of 24 ga. galvanized steel for mounting purposes.	<b>DW-5015</b>	<b>B-NW</b>	<b>AHA GYP</b>	NA	<b>RDW</b>	NA	<b>L-DWR</b>	<b>CAD-DW</b>	NA	<b>RW</b>
 <b>WBCA PL 500 Series</b>	<b>Plaster Bead.</b> 14 ga. Steel, Frame is 16 ga. Steel, 3" wide expanded flange 24 ga. galvanized material, space from the expanded flange to 1/4" safety edge will accommodate 1 3/4" of plaster	<b>PS-5030</b>	<b>B-NP</b>	<b>AHD PLY</b>	<b>ML</b>	<b>DSC-214PL</b>	<b>PW</b>	<b>L-PSW</b>	<b>CAD-FL-PL</b>	<b>3200 K</b>	NA
 <b>"WBCA AP 510 Series</b>	<b>Recessed Plaster Bead.</b> 14 ga. steel. Door is recessed 1" and lined with expanded metal lath. Frame is 16 ga. steel w/ 24 ga. galvanized casing bead and expanded metal lath surrounding door"	<b>AP-5010</b>	<b>B-RP</b>	<b>AHA-PLY</b>	<b>AP</b>	<b>DSC-210PL</b>	<b>CP</b>	<b>L-APC</b>	<b>CAD-PL</b>	<b>3206 (AP)</b>	<b>RP</b>
 <b>WBCA AT 600 Series</b>	<b>Accoustical Tile</b> (not available in drywall) 14. ga. steel. Door is recessed to accommodate up to 1" thick acoustical tile, Frame is 16 ga. Steel, Continuous piano hinge opens 180°	<b>AT-5020</b>	<b>B-RA</b>	<b>AHA</b>	<b>AT</b>	<b>DSC-210</b>	<b>CT</b>	<b>L-CPA</b>	<b>CAD</b>	<b>3205 (AT)</b>	<b>RA</b>
 <b>WBCA ATR 610 Series</b>	<b>Fire-Resistive Ceiling for Accoustical Tile</b> (not available in drywall) 16 ga. steel recessed 1-1/2", Frame is 16 ga. steel, hat channel type shape Continuous piano hinge allowing 180°	NA	NA	NA	<b>CFR</b>	<b>KATR</b>	NA	<b>L-CPB</b>	<b>CAD-FR</b>	<b>3204 (ATR)</b>	NA



### WILLIAMS BROTHERS CORPORATION OF AMERICA








Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502  
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: [www.wbdoors.com](http://www.wbdoors.com)

For country of manufacture of all Williams Brothers products please call us or visit our website at [www.wbdoors.com](http://www.wbdoors.com)

# CROSS REFERENCE ACCESS DOOR

3

## ACCESS DOORS (FR PRE, FR, FRU, FR DW, FR PL, FRB, FRC)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p><b>WBCA FR PRE 700 Series</b></p>	<b>Premium Heavy Duty. Fire-Rated/Walls Only</b> 14 ga. steel. Inside door has rolled safety edges for protection, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), between two pieces of 22 ga. steel, Continuous piano hinge allows opening to 180°	NA	B-ST	NA	NA	NA	HGFD	NA	NA	NA	FST
 <p><b>WBCA FR 800 Series</b></p>	<b>Standard. Fire-Rated/Walls &amp; Ceilings</b> 18 ga. Steel, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), in between two pieces of 22 ga. steel	FW-5050	B-IT	PFI	FRC	KRP-150FR	FD	L-FRAP	MPFR	NA	IT
 <p><b>WBCA FRU 810 Series</b></p>	<b>Standard Ultra. Fire-Rated/Walls &amp; Ceilings</b> 18 ga. Steel, Frame is 16 ga. steel, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), in between two pieces of 22 ga. Steel, Fully concealed, pivot rod type hinge. Allows opening to 140°	NA	NA	NA	NA	NA	NA	NA	NA	3218 (UFR)	NA
 <p><b>WBCA FR DW 820 Series</b></p>	<b>Fire-Rated/Walls &amp; Ceilings Drywall Bead.</b> 18 ga. steel, IFrame is 16 ga. steel, 1" wide perforated flange of 24 ga galvanized material for mounting purposes, 2 1/2" deep, Insulation is 2" thick mineral wool (ThermaFiber®), between two pieces of 22 ga. steel	NA	B-IW	PFI GYP	FRC-GB	KRP-350FR	FDWB	NA	MPFR-DW	NA	IW
 <p><b>WBCA FR PL 830 Series</b></p>	<b>Fire-Rated/Walls &amp; Ceilings Plaster Bead.</b> 18 ga. steel, Frame is 16 ga. steel, 3" wide perforated flange of 24 ga. galvanized material for mounting, space from expanded flange to 1/4" safety edge of door accommodates 1" plaster, 2 1/2" deep, Insulation: 2" thick mineral wool (ThermaFiber®), contained within door cavity	NA	B-IP	NA	NA	NA	FDPW	NA	NA	NA	IP
 <p><b>WBCA FRB 900 Series</b></p>	<b>Fire-Rated/Walls Only Uninsulated</b> 14 ga. steel. Fram is 16 ga. steel, 2 1/2" deep, Hinge is Continuous piano hinge. Allows opening to 180°. Latches are Self-latching direct action latch accepts both key and knurled knob"	FB-5060	B-UT	PFN	FR	KRP-250FR	NA	NA	MFRU	NA	UT
 <p><b>WBCA FRC 50 Series</b></p>	<b>SPECIAL ONLY - Fire-Rated Ceiling</b> 16 ga. steel recessed pan, Frame is 16 ga. steel, hat channel configuration, Insulation is 1/2" ceramic fiberboard, Hinge: Continuous piano hinge on long side of door, Latches are Self-latching, both key and knurled knob	NA	NA	NA	NA	NA	NA	NA	NA	3210 (CFRAD)	NA












### WILLIAMS BROTHERS CORPORATION OF AMERICA

Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502  
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: [www.wbdoors.com](http://www.wbdoors.com)

For country of manufacture of all Williams Brothers products please call us or visit our website at [www.wbdoors.com](http://www.wbdoors.com)

## ACCESS DOORS (MD SEC, HG SEC, GY, TB, MAP, DUCT, EXT)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p>A special snake eye screwdriver is required to open this door</p> <p><b>WBCA MD SEC 1000 Series</b></p> 	<p><b>Medium Security Access Door</b> 12 ga. steel door, 16 ga. steel frame, semi-concealed piano hinge. Counter sunk tamperproof screws, snake eye screwdriver is required. (not included)</p>	<b>MS-7000</b>	<b>PSM</b>	<b>B-MT</b>	<b>SLK</b>	<b>DSB-123</b>	<b>SP</b>	<b>L-DPM</b>	<b>MI-SAD</b>	<b>3211-200</b>	<b>MT</b>
 <p>Prepped for detention lock with paracentric key</p> <p><b>WBCA HG SEC 1100 Series</b></p> 	<p><b>High Security Access Door</b> 10 ga. door, 2" x 2" x 3 1/16" angle frame, heavy duty butt hinges. Prepped for detention lock with paracentric key. (not included)</p>	<b>SD-6000</b>	<b>PSH</b>	<b>B-HS</b>	<b>SLA</b>	<b>DSB-123-SD</b>	<b>HSP</b>	<b>L=DPH</b>	<b>MI-SADH</b>	<b>3211</b>	<b>HS</b>
 <p><b>WBCA GY 3000 Series</b></p>	<p><b>Lightweight Gypsum Ceiling Panel</b> Exceeds all required specifications that the market expects. 5/8" lightweight Gypsum drop-in-door.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA TB 1200 Series</b></p>	<p><b>Drop-In Ceiling Access Door</b> 16 ga. steel, continuous piano hinge, flush, stainless steel cam latch. Drops into the T-Bar ceiling grid. White baked enamel coat. Comes with mounting screws.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA MAP Plastic</b></p>	<p><b>Reversible Access Door</b> High impact ABS plastic. Door locked to return frame with snap friction catch, removable panel, tile-able.</p>	NA	NA	<b>B-PL</b>	NA	<b>HA</b>	NA	NA	<b>PA</b>	NA	<b>PL</b>
 <p><b>WBCA ADC/ADH 1400 Series</b></p>	<p><b>True Fit Duct Access Door</b> 22 ga steel flanged frame, 22 ga steel door. ADH-D - continuous hinge, ADC-D - no hinge.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
 <p><b>WBCA EXT 1300 Series</b></p>	<p><b>Uncomparable Exterior Access Door.</b> 16 ga. steel door, trim 1-1/2" wide, 16 ga. steel frame, 2-3/8" depth Insulation: Double layer of 1" GreenGuard® Extruded Polystyrene insulation board, with R-Value @ 75°F Mean 5.0 x 2, FM approved.</p>	<b>LT-4000</b>	NA	<b>B-XT</b>	NA	<b>MX</b>	NA	<b>L-XT</b>	<b>WID</b>	NA	<b>XT</b>




## WILLIAMS BROTHERS CORPORATION OF AMERICA

Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502  
Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: [www.wbdoors.com](http://www.wbdoors.com)

For country of manufacture of all Williams Brothers products please call us or visit our website at [www.wbdoors.com](http://www.wbdoors.com)

## ACCESS DOORS (WIN)

WBCA Product Number	Description	Acudor #	Babcock #	Cendrex #	Elm #	Karp #	J.L. Ind #	Larson #	Mifab #	Milcor #	Nystrom #
 <p><b>WBCA WIN 1700 Series</b></p>	<p><b>Insulated Walk-In Duct Door</b>            20 ga. galvanized steel door, 16 ga galvanized steel frame. 1" 3lb density insulation. 2 exterior latches with interior handles. 1/2" neoprene closed cell door to frame gasketing.</p>	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

**WILLIAMS BROTHERS CORPORATION OF AMERICA**

Corporate Office 1330 Progress Drive, Front Royal, VA 22630 Western Distribution Center 4058 S. McCarran Blvd., Bldg.A, Reno, NV 89502  
 Phone: 1-800-255-5515 • Fax: 1-800-822-5001 • Website: [www.wbdoors.com](http://www.wbdoors.com)

For country of manufacture of all Williams Brothers products please call us or visit our website at [www.wbdoors.com](http://www.wbdoors.com)